



Mototamburo 165E, Ø 165 mm

50 Hz

Motore			Velocità nominale a pieno carico a 50 Hz m/sec	Coppia Nm	Forza tangenz. N	Max. carico radiale T1+T2 N	Peso in kg per lunghezze STANDARD																			Tipo di supporti
Potenza kW/HP	Poli n.	Stadi riduttore n.					RL in mm																			
							350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100	per 50 mm up to 1800			
0.11/0.15	12	3	0.05	170	2070	9330	29	30.5	32	33	34	35	36.5	38	39	40	41.5	43	44	46	47	Disponibile a richiesta	KL40			
			0.06	141	1700																					
			0.08	113	1375																					
			0.10	86	1045																					
0.37/0.50	6	3	0.13	239	2905	9330	30	31.5	33	34	35	36	37.5	39	40	41	42.5	44	45	47	48					
			0.16	193	2345																					
	4	3	0.20	157	1910	9330	26	28	29.5	31	32	33	34	35.5	37	38	39	40.5	42	43	45			46		
			0.25	127	1545																					
			0.32	97	1175																					
			0.40	77	930																					
		2	0.50	60	735																					
			0.63	49	595																					
			0.80	38	455																					
			1.00	29	360																					
0.75/1.00	6	3	0.16	341	4140	9330	33	34.5	36	37	38	39	40.5	42	43	44	45.5	47	48	50	51					
			0.20	302	3665																					
	4	3	0.25	248	3005	9330	31	32.5	34	35	36	37	38.5	40	41	42	43.5	45	46	48	49					
			0.32	189	2295																					
			0.40	162	1815																					
			0.50	119	1435																					
		2	0.63	96	1160																					
			0.80	72	885																					
			1.00	57	700																					
			1.10/1.50	4	3																	0.25	332	4030	9330	34
0.32	272	3305																								
2	3	0.40		226	2745	9330	33	34.5	36	37	38	39	40.5	42	43	44	45.5	47	48	50	51					
		0.50		183	2220																					
		0.63		139	1690																					
		0.80		110	1340																					
	2	1.00		87	1060																					
		1.25		70	855																	8700				
		1.60		54	650																					
		2.00		42	515																		6950			
2.50	34	420																								
1.50/2.00	3	0.50	237	2880	9330	34	35.5	37	38	39	40	41.5	43	44	45	46.5	48	49	51	52						
		0.63	195	2360																						
		0.80	154	1870																						
		1.00	122	1480																						
	2	2	1.25	98	1195	8700																				
			1.60	75	910																					
			2.00	59	720		6950																			
		2.50	48	585																						
		3.15	39	485																						

Motore	Max. carico radiale T1+T2 N	Peso in kg per lunghezze STANDARD																	Tipo di supporti
		RL in mm																	
		300	320	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	per 50 mm fino a 1800 Disponibile a richiesta	
Tamburo folle UT165E	9330	12.5	14.0	15.5	17.0	18.5	20.0	21.5	23.0	24.5	26.0	27.5	29.0	30.5	32.0	33.5	35.0	KL40	