



# Mototamburo 400L, Ø 400 mm

# 50 Hz

Motore			Velocità nominale a pieno carico a 50 Hz m/sec	Coppia Nm	Forza tan-genz. N	Max. carico radiale T1+T2 N	RL min. speciale	Tipo	Peso in kg per dimensioni STANDARD												Tipo di supporto
Potenza kW/HP	Poli n.	Stadi riduttore n.							RL in mm (RL >2000 mm disponibile su richiesta)												
									500	550	600	650	700	750	800	850	900	950	1000	per 50 mm fino a 2000	
2.20/ 3.00	4	2	0.80	522	2584	20000	500	400L	120	125	130	135	140	145	150	155	160	165	170	5 kg	KL41-HD
			1.00	418	2090																
			1.25	334	1670																
			1.60	265	1325																
			2.00	209	1045																
2.50	167	835																			
3.00/ 4.00	4	2	0.80	712	3562	20000	500	400L	130	135	140	145	150	155	160	165	170	175	180	5 kg	KL41-HD
			1.00	570	2850																
			1.25	456	2280																
			1.60	356	1780																
			2.00	285	1425																
2.50	228	1140																			
4.00/ 5.50	4	2	0.80	950	4750	20000	500	400L	130	135	140	145	150	155	160	165	170	175	180	5 kg	KL41-HD
			1.00	760	3800																
			1.25	608	3040																
			1.60	475	2375																
			2.00	380	1900																
2.50	304	1520																			
5.50/ 7.50	4	2	1.25	836	4180	20000	500	400L	130	135	140	145	150	155	160	165	170	175	180	5 kg	KL41-HD
			1.60	653	3265																
			2.00	524	2620																
			2.50	418	2090																
7.50/ 10.00	2	2	2.00	712	3525	20000	500	400L	130	135	140	145	150	155	160	165	170	175	180	5 kg	KL41-HD
			2.50	570	2822																
			3.15	452	2238																

<b>Tamburo folle</b>	20000	500	UT400L	80	85	90	95	100	105	110	115	120	125	130	5 kg	KL41-HD
----------------------	-------	-----	--------	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	------	---------



# Mototamburi 400M & 400H, Ø 400 mm

## 50 Hz

Motore			Velocità nominale a pieno carico a 50 Hz m/sec	Coppia Nm	Forza tan- genz. N	Max. carico radiale T1+T2 N	RL min. speciale	Tipo	Peso in kg per dimensioni STANDARD												Tipo di supporto								
Potenza kW/HP	Poli n.	Stadi ridut- tore n.							RL in mm (RL >2000 mm disponibile su richiesta)																				
									500	550	600	650	700	750	800	850	900	950	1000	per 50 mm fino a 2000									
2.20/ 3.00	8	3	0.16	2638	13062	50000	650	400H																6 kg	KL60				
			0.20	2111	10450																								
			0.25	1688	8360																								
	4.00/ 5.50	8	2	0.32	1306	6465	40500	600	400M																6 kg	KL60			
				0.40	1045	5173																							
				0.50	836	4139																							
				0.63	663	3282																							
0.80			522	2584																									
1.00			418	2090																									
1.25			334	1670																									
1.60	265	1325																											
5.50/ 7.50	8	3	0.25	3070	15200	50000	650	400H																6 kg	KL60				
			0.32	2399	11875																								
			0.40	1919	9500																								
	4	2	0.50	1520	7525	40500	600	400M																6 kg	KL60				
			0.63	1206	5970																								
			0.80	960	4750																								
			1.00	760	3800																								
1.25	608	3040																											
1.60	475	2375																											
5.50/ 7.50	4	3	0.40	2638	13063	50000	650	400H																6 kg	KL60				
			0.50	2111	10450																								
			0.63	1675	8294																								
	2	2	0.80	1306	6465	40500	600	400M																6 kg	KL60				
			1.00	1045	5173																								
			1.25	844	4180																								
			1.60	660	3265																								
2.00	528	2620																											
2.50	422	2090																											
3.15	332	1659																											
7.50/ 10.00	6	3	0.50	2878	14250	50000	710	400H															6 kg	KL60					
			0.63	2284	11310																								
	4	2	0.80	1799	8906	40500	600	400M																6 kg	KL60				
			1.00	1425	7054																								
			1.25	1140	5644																								
			1.60	891	4411																								
			2.00	712	3525																								
2.50	570	2822																											
3.15	452	2238																											
11.00/ 15.00	4	3	0.80	2638	13063	50000	710	400H															6 kg	KL60					
			1.00	2111	10450																								
	2	2	1.25	1688	8360	40500	660	400M																6 kg	KL60				
			1.60	1306	6465																								
			2.00	1045	5173																								
			2.50	844	4180																								
			3.15	660	3265																								
2	3	1.00	2878	14250	50000	710	400H																6 kg	KL60					
		1.25	2303	11400																									
		1.60	1799	8906																									
		2.00	1439	7125																									
2	2	2.50	1142	5700	40500	660	400M															6 kg	KL60						
		3.15	907	4523																									

Tamburo folle	40500	600	UT400M			113	119	126	132	138	142	148	154	160	6 kg	KL60
	50000	650	UT400H			124	131	137	143	147	153	159	165	6 kg	KL60	