



# OPTIONAL EXTRAS

## Motorized Pulley 138E

### Specifications

138E

|   |                               |             |
|---|-------------------------------|-------------|
| Total stainless steel option AISI 304 range   | Re-greasable labyrinth seals! | x           |
| Food grade oil & grease - FDA & USDA recognized - available on request  |                               | x           |
| Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. According to European Directive 94/9/EC. |                               | On request! |
| TOTAL acid resistant stainless steel option - AISI 316  |                               | x           |
| Black rubber lagging - STANDARD specifications:<br>- Smooth lagging - Hardness 60 ±5 Shore A<br>- Diamond lagging - Hardness 60 ±5 Shore A          |                               | o           |
| White smooth rubber lagging (FDA). Oil, fat & grease resistant  |                               | o           |
| SPECIAL lagging available on request - e.g. hot vulcanized etc.   |                               | o           |
| Single phase motors available on request  |                               | x           |
| Electromagnetic brake   |                               | x           |
| Min. RL dimensions by (mm)  |                               | 50          |
| Mechanical backstop   |                               | x           |
| Modified for vertical mounting  |                               | o           |
| Modified for mounting between 5° - ≤90° - e.g. for magnetic separators  |                               | o           |
| Insulation class F - Allowable ambient temperature: -25°C/+40°C   |                               | Std.        |
| Insulation class H with synthetic oil - Allowable ambient temperature: -25°C/+40°C  |                               | x           |
| Low noise drives for noise sensitive areas  |                               | x           |
| Parallel shell  |                               | x           |
| Thermal protector   |                               | Std.        |
| IP66/67 Compact stainless steel - AISI 304 or 316 range - terminal box  |                               | x           |
| Straight or elbow connector with flying lead  |                               | x           |
| Straight connector with flying lead - Stainless steel - AISI 304 range  |                               | x           |
| Shaft sealing system - degree of protection IP66/67 (EN60034-5)   |                               | Std.        |
| Screened cables - a MUST together with Frequency Converters   |                               | x           |
| Euro wide range voltage (3x220-240V / 380-415V 50 Hz) with +/-10% tolerance - DIN IEC 38 or (3x380-400V / 660-690V 50 Hz)                           |                               | Std.        |
| Special voltages - 50 and/or 60 Hz Please specify!  |                               | x           |
| CSA approved motors - available on request only!  |                               | x           |

X = Optional extras

o = Available as option with certain limitations. Please refer to Technical precautions pages 81-92!

Std. = Fitted as standard