



OPTIONAL EXTRAS

Motorized Pulley 500L, 500M & 500H

Specification		500L	500M & 500H
Semi-rust-free option	Re-greasable labyrinth seals!	TS11	TS11
Semi-rust-free option	Standard seals!	TS12	TS12
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. According to European Directive 94/9/EC.		On request!	On request!
Black rubber lagging - STANDARD specifications:		o	o
- Smooth lagging - Hardness 60 ±5 Shore A		8 mm	8 mm
- Diamond lagging - Hardness 60 ±5 Shore A		8 mm	8 mm
White smooth rubber lagging (FDA). Oil, fat & grease resistant		x	x
SPECIAL lagging available on request - e.g. hot vulcanized, ceramic etc.		x	x
Electromagnetic brake		x	x
Min. RL dimensions increases by (mm)		100	100
Mechanical backstop	500L from RL750mm & 500M from RL800 mm	x	x
Insulation class F - Allowable ambient temperature: -25°C - +40°C		Std.	Std.
Insulation class H with synthetic oil		x	x
Parallel shell		x	x
Thermal protector		Std.	Std.
IP66/67 cast iron terminal box painted yellow		Std.	Std.
Shaft sealing system - degree of protection IP66/67 (EN60034-5)		Std.	Std.
3-phase single voltage (3 x 400V) or (3 x 690V), 50 Hz, with +/-10% tolerance - DIN IEC 38		Std.	Std.
Special voltages - 50 and/or 60Hz Please specify!		x	x
Dual voltage - delta/star - connection possibility!		x	x
CSA approved motors - available on request only!		x	x

x = Optional extra's

o = An option with certain limitations. Please refer to Technical precautions pages 81-92!

Std. = Fitted as standard