



2 Rollers

series Impact



Øe 89 NA

Base roller:

MPS/1

D = 60;
spindle 15; d₁ = 20
bearing 6202
ch = 17

PSV/1-FHD

D = 63;
spindle 20; d₁ = 20
bearing 6204
ch = 14

belt	roller						rings width
	width mm	dimensions mm			weight Kg		
arrangements	B	C	A	MPS/1-FHD	PSV/1-FHD	E = 35	
400	160	168	186	1.8	2.3		
300 500	200	208	226	2.1	2.7		
400 650	250	258	276	2.6	3.3		
500 800	315	323	341	3.3	4.1		
300 650 1000	380	388	406	3.9	4.8		
800 1200	465	473	491	4.6	5.6		
400	500	508	526	5.1	6.1		
1400	530	538	556		6.4		
500 1000	600	608	626	6.1	7.2		
1200	700	708	726	6.9	8.1		
650	750	758	776	7.4	8.8		
1400	800	808	826		9.2		
800	950	958	976	9.3	10.9		
1000	1150	1158	1176	11.1	12.9		
1200	1400	1408	1426	13.5	15.7		
1400	1600	1608	1626		17.9		

Example of ordering
standard design
MPS/1,15B,89NA,323

for special designs
see pages 80-81