

Øe 159 NA

Base roller:

PSV/1-FHD

D = 89;
spindle 20; d₁ = 20
bearing 6204
ch = 14

PSV/4-FHD

D = 89;
spindle 30; d₁ = 30
bearing 6206
ch = 22

PSV/2-FHD

D = 89;
spindle 25; d₁ = 25
bearing 6205
ch = 18


PSV/5-FHD

D = 89 x 4*;
spindle 30; d₁ = 30
bearing 6306
ch = 22

PSV/3-FHD

D = 89;
spindle 25; d₁ = 25
bearing 6305
ch = 18

* biggertubethickness
than standard

belt	roller										rings width
	width mm	dimensions mm			weight Kg						
arrangements											E = 50
	B	C	A	PSV/1-FHD	PSV/2-FHD	PSV/3-FHD	PSV/4-FHD	PSV/5-FHD			
800	315	323	*	7.3	7.9	8.2	9.0	9.0			
1000	380	388	*	8.4	9.2	9.5	10.4	11.0			
800 1200	465	473	*	10.4	11.3	11.6	12.6	12.2			
1400	530	538	*	11.6	12.5	12.9	14.0	14.6			
1000 1600	600	608	*	13.4	14.5	14.8	16.1	16.7			
1800	670	678	*		15.8	16.2	17.5	18.1			
1200	700	708	*	15.5	16.7	17.1	18.5	19.1			
2000	750	758	*	16.6	17.8	18.2	19.7	20.3			
1400	800	808	*	17.7	19.0	19.3	20.9	21.5			
1600	900	908	*	19.8	21.2	21.6	23.3	23.9			
800	950	958	*	20.6	22.3	22.7	24.5	25.1			
1800	1000	1008	*		23.4	23.8	25.7	26.3			
2000	1100	1108	*			26.0	28.1	28.7			
1000	1150	1158	*	25.0	26.8	27.2	29.3	29.9			
1200	1400	1408	*	30.3	32.4	32.8	35.4	36.0			
1400	1600	1608	*	35.1	37.5	37.9	40.8	41.4			
1600	1800	1808	*	39.3	42.0	42.4	45.6	46.2			
1800	2000	2008	*		46.5	46.9	50.5	51.1			
2000	2200	2208	*			51.3	55.3	59.9			

* in relation to the choice of base roller

Example of ordering
standard design
PSV/4-FHD,30F,159NA,473

for special designs
see pages 80-81