



# Øe 194 NA

Base roller:

## PSV/5-FHD

D = 133;  
spindle 30; d<sub>1</sub> = 30  
bearing 6306  
ch = 22

## PSV/7-FHD

D = 133 x 6\*;  
spindle 40; d<sub>1</sub> = 4  
bearing 6308  
ch = 32

\* bigger tube  
thickness than  
standard

belt	roller						
	width mm	dimensions mm			weight Kg		rings width
arrangements	B C A			PSV/5-FHD	PSV/7-FHD	E = 50	
	1600	600	608	632	23.4	28.1	
	1800	670	678	702	25.5	30.5	
	2000	750	758	782	28.6	34.0	
	2200	800	808	832	30.3	35.9	
1600	2400	900	908	932	33.8	39.8	
	2600	950	958	982	35.5	41.8	
	1800	1000	1008	1032	37.2	43.7	
	2800	1050	1058	1082	39.0	45.7	
	2000	1100	1108	1132	40.7	47.6	
	3000	1120	1128	1152	41.1	48.1	
	2200	1250	1258	1282	45.9	53.5	
	2400	1400	1408	1432	51.1	59.3	
	2600	1500	1508	1532	54.6	63.2	
	2800	1600	1608	1632	58.1	66.9	
1600		1800	1808	1832	65.0	74.9	
1800		2000	2008	2032	71.9	82.7	
2000		2200	2208	2232	78.9	90.5	
2200		2500	2508	2532	89.3	102.2	
2400		2800	2808	2832	99.7	113.9	
2600		3000	3008	3032	106.6	121.7	
2800		3150	3158	3182	111.8	127.5	

Example of ordering  
standard design  
PSV/5-FHD,30F,194NA,678

for special designs  
see pages 80-81