



series

TOP C/2
TOP V/2

Ø 127PE
Ø 127NPE*

Bearing 6205
(25 x 52 x 15)

d = 25
ch = 18
s = 10,5
e = 4
g = 12

Example of ordering
standard design
TOP/C2 25F 127PE 323
Contactless execution,
HDPE shell
TOP/V2 25F 127PE 473
Hermetic execution, HDPE
shell

TOP/C2 25F 127NPE 708
Contactless execution,
reinforced shell HDPE+steel
TOP/V2 25F 127NPE 708
Hermetic execution,
reinforced shell HDPE+steel

For special shaft executions
see pages 80-82-83

belt	roller			weight		load capacity					
	width mm	dimensions mm			Kg		daN				
arrangements 	B	C	A	rotating parts	total	belt speed m/s					
				1	1,5	2	2,5	3	4		
400	160	168	192	1,08	1,91	309	309	289	268	252	229
300 500	200	208	232	1,22	2,21	309	309	289	268	252	229
400 650	250	258	282	1,41	2,58	309	309	289	268	252	229
500 800	315	323	347	1,65	3,07	309	309	288	268	252	229
300 650 1000	380	388	412	1,88	3,56	309	309	288	267	251	228
800 1200	465	473	497	2,20	4,20	309	309	288	267	251	228
400	500	508	532	2,32	4,47	295	295	288	267	251	228
1400	530	538	562	2,43	4,69	276	276	276	267	251	228
500 1000	600	608	632	2,69	5,22	239	239	239	239	239	227
1200	700	708	732*	5,93	8,84	197	197	197	197	197	197
650	750	758	782*	6,36	9,47	182	182	182	182	182	182
1400	800	808	832*	6,79	10,09	169	169	169	169	169	169
800	950	958	982*	8,08	11,96	138	138	138	138	138	138
1000	1150	1158	1182*	9,80	14,46	109	109	109	109	109	109
1200	1400	1408	1432*	11,96	17,58	85	85	85	85	85	85
1400	1600	1608	1632*	13,68	20,07	70	70	70	70	70	70

* TOP rollers lengths with reinforcing internal steel tube